

Bearings Symbol	d	D	B	C	T	r (min)	r1 (min)	a	Load Rating (daN)		Max Speed RPM
									Dynamic (C)	Static (Co)	
30203	17	40	12	11	13.25	1	1	3.5	2080	1900	9800
30204	20	47	14	12	15.25	1	1	4	3100	3150	8400
30205	25	52	15	13	16.25	1	1	3.5	3600	3950	7500
30206	30	62	16	14	17.25	1	1	3.5	4600	4900	6300
30207	35	72	17	15	18.25	1.5	1.5	3	5800	6200	5300
30208	40	80	18	16	19.75	1.5	1.5	3	6000	6400	4800
30209	45	85	19	16	20.75	1.6	1.6	3	6700	7400	4300
30210	50	90	23	19	24.75	1.5	3	3.75	82500	100000	4300
30214	70	125	24	21	26.25	1.5	2	1	12000	14000	2800
30215	75	130	25	22	27.25	1.5	2	0.5	13600	16600	2700
30302	15	42	13	11	14.25	1.0	1.5	4.57	2330	2070	9000
30305	25	62	17	15	18.25	1.5	1.5	5.5	4600	4300	6700
30306	30	72	19	16	20.75	1.5	1.5	4.5	5500	5200	5600
30308	40	90	23	20	25.25	1.5	2	5.45	8900	9600	4300
30312	60	130	31	26	33.5	2.5	3	7.5	15000	16000	2900
31312	59.985	34.983	30.925	21.948	33.449	3.5	3.5	7	152000	172000	3200
32207	35	72	23	19	24.25	1.5	1.5	6	7000	8000	5300
32208	40	80	23	19	24.75	1.5	1.5	5	7800	8800	4800
32210	50	90	23	19	24.75	1.5	1.5	4	9300	11300	4000
32211	55	100	25	21	26.75	1.5	2	3	10650	13140	3600
32212	60	110	28	24	29.75	1.5	2	5.75	12720	16030	3400
32213	65	120	31	27	32.75	0.8	3.5	5	15550	19550	3200
32214	70	125	31	27	33.25	1.5	2	5.25	15770	20760	3800
32216	80	140	33	28	35.25	2	2.5	4.5	17700	21900	2500
32217	85	150	36	30	38.5	2	2.5	3.5	21500	28500	2400
32307	35	80	31	25	32.75	1.5	2	12.5	10000	10800	5000
32308	40	90	33	27	35.25	1.5	2	11.7	11500	13300	4300
32309	45	100	36	30	38.25	1.5	2	10.5	14200	17700	3900
32312	60	130	46	37	48.5	2.5	3	16	22300	27000	2900
33010	50	80	24	19	B	1	2.1	7	7150	10250	5300
33111	55	95	30	23	30	1.6	1.6	8	11300	15500	3800
418/414	38.1	88.501	29.083	22.225	26.988	1.5	3.6	10.1	10300	11500	4800
565/562	63.5	130	33.937	28	36.937	3.5	6.5	8.937	19000	22430	3400

580/572	82.55	139.992	36.098	28.575	36.512	3.3	3.6	5.2	17600	22000	2400
683/672	95.25	168.275	41.275	30.162	41.275	3.3	3.5	6.275	23400	36600	2800
11590/11520	15.875	42.863	14.288	9.525	14.288	1.6	1.6	1.28	1570	1600	8500
15123/15245	31.75	62	19.05	14.288	18.161	1.3	4	6	4850	5750	6000
1988/1922	28.575	57.15	19.355	15.875	19.845	1.5	3.5	5.845	4800	5600	6700
25877/25821	34.925	73.025	24.608	19.05	23.812	0.8	1.5	8.812	7210	8800	5300
02872/02820	28.575	73.025	22.225	17.462	22.225	3.2	0.8	4	5400	6400	-
47487T/ 47420T	69.863	120	32.6	26.25	32.545	0.8	3.5	7.1	15700	23000	-
LM501349/ LM501310	41.275	73.431	19.812	14.732	19.558	0.8	3.5	2.758	5590	7000	4800
LM48548/ LM48510	34.925	65.088	18.288	13.97	18.034	1.3	3.6	4	4250	5550	5600
LM603049/ LM603012	45.242	77.788	19.842	16.667	21.43	0.8	3.5	-	5450	6900	-
M86649/ M86610	30.162	64.292	21.48	16.67	21.433	1.5	1.5	3.433	4950	6100	6000
M88048/ M88010	33.338	68.262	22.225	17.462	22.225	1.5	0.8	3.225	5500	6950	4600
M802048/ M802011	41.275	82.55	26.543	20.193	26.543	3.3	3.5	4.543	7500	9500	4500

INDEX : d - Bore Diameter, D - Outer Diameter, B - Bearing Width, r - Corner Radius, RPM - Revolution / Minute